



## Wand Swivels



**Easy Turn Gun Swivels for High Pressure Spray Wands** are high quality, Swiss-Made, construction. Rated to 4000 PSI & 250° F. Nickel-plated brass body, stainless steel bearing. Available in 1/4" and 3/8" sizes in male thread, (MPT) and female thread, (FPT). Nitrile o-ring.


Part No.	Ports	Max. PSI
MM 32557	1/4" FPT x 1/4" FPT	4000
MM 32552	1/4" MPT x 1/4" FPT	4000
MM 32569	3/8" FPT x 3/8" FPT	4000
MM 32769	3/8" FPT x 3/8" FPT	7300
MM 32564	3/8" MPT x 3/8" FPT	4000
MM 32852	* 3/8" MPT x 3/8" FPT	4000
MM 32764	3/8" FPT x 3/8" FPT	7300
MM 32563	3/8" MPT x 3/8" MPT	4000
MM 32763	3/8" MPT x 3/8" MPT	7300
MM 32562	3/8" MPT x 1/4" FPT	4000
MM 32561	3/8" MPT x 1/4" MPT	4000
MM 32863	1/2" MPT x 1/2" MPT	4000
MM 32864	1/2" MPT x 1/2" FPT	4000
MM 32894	1/2" MPT x 1/2" FPT	7300

\* 3/8" Flow Path.

**CALL for CURRENT PRICING**



## Flanged Style High Pressure Swivels




**High Quality, Flanged Style Swivels** for surface cleaners, fire applicators, under carriage wash, etc. Brass, Nickel-plated construction. Standard with Carbide seals rated to 250° F.

Part No.	Ports	Max. PSI	Max. RPM	Maximum Temperature
MM 58051	1/4" F x 1/4" M	4000	2000	250° F.
MM 58153	3/8" F x 3/8" M	4000	2000	250° F.
MM 38051	1/4" F x 1/4" M	2000	2000	250° F.
MM 38153	3/8" F x 3/8" M	2000	2000	250° F.

**Call Toll Free For Prices**



## Bulkhead Style High Pressure Swivels




**High Quality, Bulkhead Swivels** for surface cleaners, tire applicators, under carriage wash, etc. Brass, Nickel-plated construction. **37 Series** is standard with Ceramic seals. **57 Series** is standard with Carbide seals.

Part No.	Ports	Max. PSI	Max. RPM	Maximum Temperature
MM 33051	1/4" F x 1/4" M	4000	1000	100° F.
MM 33153	3/8" F x 3/8" M	4000	1000	100° F.
MM 37051	1/4" F x 1/4" M	2500	2000	250° F.
MM 37153	3/8" F x 3/8" M	2500	2000	250° F.
MM 57051	1/4" F x 1/4" M	4000	2000	250° F.
MM 57153	3/8" F x 3/8" M	4000	2000	250° F.


**Call Toll Free For Prices**

## High Pressure Gun Swivels

**High Pressure Gun Swivels.** Brass or stainless steel construction. Rebuildable design. Rated to 200° F. Brass rated to 3,000 PSI. Stainless rated to 5,000 PSI.



7080



7044

Part No.	Material	Size	Max. PSI
AA 7045	Brass	3/8" F x F	3000
AA 7080	Brass	3/8" M x F	3000
AA 7044	Stainless	3/8" M x F	5000
AA 7084	Repair Kit for above swivels .....		




## Inline Swivels


**Inline Swivels** from Mosmatic feature Swiss Engineering and are designed for high flow water and air applications. Buna seals are standard, but EPDM is available.

**DGE Series** feature Nickel-Plated Brass bodies, one bearing design. Rated to 4000 PSI and 250° F. Maximum of 30 RPM.

**DGR Series** feature Stainless Steel bodies, 4 Bearing design. Rated to 3000 PSI and 180° F. RPM varies with size.



DGE MxF



DGR FxF

### DGE Series

Part No.	Ports	Construction	Max RPM
MM 34853	1/2" M x F	Nickel-Plated Brass	30
MM 34863	1/2" F x F	Nickel-Plated Brass	30
MM 34854	3/4" M x F	Nickel-Plated Brass	30
MM 34864	3/4" F x F	Nickel-Plated Brass	30
MM 34855	1" M x F	Nickel-Plated Brass	30
MM 34865	1" F x F	Nickel-Plated Brass	30
MM 34856	1-1/4" M x F	Nickel-Plated Brass	30
MM 34866	1-1/4" F x F	Nickel-Plated Brass	30
MM 34857	1-1/2" M x F	Nickel-Plated Brass	30
MM 34867	1-1/2" F x F	Nickel-Plated Brass	30

**Call Toll Free For Prices**

### DGR Series

Part No.	Ports	Construction	Max RPM
MM 34211	1/2" M x F	Stainless Steel	200
MM 34212	1/2" F x F	Stainless Steel	200
MM 34311	3/4" M x F	Stainless Steel	150
MM 34312	3/4" F x F	Stainless Steel	150
MM 34411	1" M x F	Stainless Steel	130
MM 34412	1" F x F	Stainless Steel	130
MM 34511	1-1/2" M x F	Stainless Steel	100
MM 34512	1-1/2" F x F	Stainless Steel	100
MM 34611	2" M x F	Stainless Steel	70
MM 34612	2" F x F	Stainless Steel	70

**Call Toll Free For Prices**



## Inline Swivels

**PARKER PS Series Inline Swivels** are designed to eliminate hose twist and torque that may cause premature hose failure. Ideal for hose reels, wash booms and industrial applications.



**Standard Features:** Sealed bearings and hardened bearing races for extended service life • Full flow design • Buna or Viton® seals • Teflon backup rings • (Chromium-6 Free) Plated carbon steel construction for added corrosion resistance • Rated to 5000 PSI and 250° F. (Up to 1" sizes) • Available in M x F or F x F NPT ports • Many other port options are available.

### Male x Female

Part No.	Size	Seal	Max. PSI
PA PS6101	3/8" M x F	Buna	5000
PA PS8101	1/2" M x F	Buna	5000
PA PS12101	3/4" M x F	Buna	5000
PA PS16101	1" M x F	Buna	5000

Viton® is a registered trademark of DuPont Performance Elastomers

Order from our entire inventory online!  
Scan our QR Code [dultmeier.com](http://dultmeier.com)



- Current Pricing
- Current Flyers
- Web Specials
- Order Status
- Closeout Items
- Parts Schematics

