

## BALDOR • RELIANCE

### Washdown Motors for Washdown Service



**Baldor-Reliance Washdown Motors** are designed to meet the demands of applications that require protection from water, moisture and contaminants. Ideal for use with high pressure washdown, food processing, outdoor applications, sanitary washdown and more.

Available with epoxy, powder-coated finish or in stainless steel construction (*stainless are food grade rated*). TEFC or TENV C-face, 56 frames are shown, but other frames and horsepower available. Doubled sealed motor bearings, neoprene gaskets for waterproof seal.

#### White Epoxy Coated

Part No.	HP	Phase	RPM	Voltage	Wt.
CE CWDL3504	1/2 TEFC	1	1800	115/230	35 lbs.
CE CWDL3507	3/4 TEFC	1	1800	115/230	36 lbs.
CE CWDL3510	1 TEFC	1	1800	115/230	41 lbs.
CE CWDL3514	1-1/2 TEFC	1	1800	115/230	50 lbs.
CE CWDM3538	1/2 TENV	3	1800	230/460	28 lbs.
CE CWDM3542	3/4 TENV	3	1800	230/460	29 lbs.
CE CEWDM3546	1 TENV	1	1800	230/460	41 lbs.
CE CEWDM3554	1-1/2 TENV	3	1800	230/460	50 lbs.
CE CEWDM3558	2 TEFC	3	1800	230/460	50 lbs.

#### Stainless Steel

Part No.	HP	Phase	RPM	Voltage	Wt.
CE CFSWDL3504	1/2 TEFC	1	1800	115/230	41 lbs.
CE CFSWDL3507	3/4 TEFC	1	1800	115/230	47 lbs.
CE CFSWDL3510	1 TEFC	1	1800	115/230	72 lbs.
CE CFSWDM3538E	1/2 TENV	3	1800	230/460	37 lbs.
CE CFSWDM3542E	3/4 TENV	3	1800	230/460	37 lbs.
CE CFSWDM3546E	1 TENV	3	1800	230/460	37 lbs.
CE CFSWDM3554E	1-1/2 TENV	3	1800	230/460	45 lbs.
CE CFSWDM3558E	2 TENV	3	1800	230/460	45 lbs.

## Motor/Pump Baseplates



**Heavy Gauge Steel or Stainless Steel Baseplates** for mounting pumps to motors or engines. All units shown are painted and ready for drilling. Baseplates are available as plates only, plates with handles or plates with wheels.

Part No.	Description	Size	Gauge	Wt. Lbs.
HY 1510-2	Baseplate only, Painted	9.5" W x 18" L	3/16"	7
DS BP1230	Baseplate only, Painted	12" W x 30" L	3/16"	27
DS BP1630	Baseplate only, Painted	16" W x 30" L	3/16"	73
DS BP1630SS	Baseplate only, Stainless	16" W x 30" L	10 ga.	27
DS BP1830SS	Baseplate only, Stainless	18" W x 30" L	10 ga.	39
DU BP4216	Baseplate only, Painted	16" W x 42" L	3/8"	91
DU BP4222S	Baseplate only, Stainless	22" W x 42" L	3/8"	94
DU BP5222	Baseplate only, Painted	22" W x 52" L	3/8"	154
DU BP5218	Baseplate only, Painted	18" W x 51" L	1/2"	176
DU BP5621	Baseplate only, Painted	21" W x 56" L	1/2"	195
DU 1796	Baseplate, Aluminum with Wheels.....	10" W x 15" L	11 ga.	15
DU 1430	Baseplate, Aluminum with Wheels.....	10" W x 20" L	11 ga.	19
DU 1980A	Aluminum, Hand Carry	12.5" W x 14" L	14 ga.	5
DU BG250SS	* Belt Guard, Stainless, 23" L x 11" H.....			
DU BG305SS	* Belt Guard, Stainless, 30" L x 15" H.....			

\* Solid Belt Guard Cover will need to be cut out for shafts.

## Carbonator Pump Motors

Designed for close-coupled pump applications. Ideal for compact pump/motor applications. Slotted 5/8" shafts are designed to accept flat-shaft pumps such as Procon or Rotoflow brands.

**Features:** 1-Phase, Open-Dripproof • 1725 RPM • Rated for continuous duty • Automatic overload protection • Frames are 48YZ • Rotation can easily be changed in the field if required.



Slotted Shaft

Part No.	Size	Voltage	Amp Rating	Wt.
CE 931	1/3 HP	115	5.6	16 lbs.
CE 932	1/2 HP	115/230	7.2/3.6	19 lbs.
CE 933	3/4 HP	115/230	10.4/5.2	25 lbs.

### Visit our office in Omaha, Nebraska



13808 Industrial Road • Omaha, NE 68137  
1-800-228-9666 • 1-402-333-1444 • FAX: 1-402-333-5546

### Visit our office in Davenport, Iowa



601 West 76th St. • Davenport, IA 52806  
1-800-553-6975 • 1-563-386-0930 • FAX: 1-563-386-5448  
email: dultmeier@dultmeier.com • website: dultmeier.com

WE APPRECIATE YOUR  
**BUSINESS!**

### Order from our entire inventory online!

- Current Pricing
- Web Specials
- Closeout Items
- Current Flyers
- Order Status
- Parts Schematics

### Scan our QR Code



www.  
dultmeier.com