

YAMADA Drum Pumps

Air-Operated Diaphragm

Air-Operated Drum Diaphragm Pumps from Yamada. Designed for versatile and cost effective transfer and dispensing of liquids from 55 gallon drums. Wide variety of chemical compatibility. Complete units include pump, standpipe, bung adapter and fittings.

Features: Self-priming • On/Off reliability • Ability to run dry • Ability to dead head • Portable • Lightweight • Aluminum, Polypropylene, Stainless and Kynar Bodies • Buna, Santoprene and Teflon Diaphragms shown, (Viton®, EPDM, Hytrel and Neoprene are also available) • Rated to 180° F. with Buna and Santoprene and 212° F. with Teflon diaphragms.



yamada

NDP-20BPS-D
NDP-20BPT-D



Part No.	Port Size	Pump Construction	Max. Flow	Max. PSI	Max. Wt.
YA DP10BAN-D	3/8"	+ Alum/Buna	5 GPM	100	10 lbs.
YA G15PS-D	1/2"	* Poly/Santo	17 GPM	70	15 lbs.
YA G15PT-D	1/2"	* Poly/Teflon	17 GPM	70	15 lbs.
YA G15AN-D	1/2"	+ Alum/Buna	16 GPM	100	17 lbs.
YA NDP-15BST-D	1/2"	* Stainless/Teflon	13 GPM	100	19 lbs.
YA NDP-15FVT-D	1/2"	† Kynar/Teflon	13 GPM	100	14 lbs.
YA NDP-20BPS-D	3/4"	* Poly/Santo	29 GPM	100	22 lbs.
YA NDP-20BPT-D	3/4"	* Poly/Teflon	29 GPM	100	22 lbs.
YA NDP-20BAN-D	3/4"	+ Alum/Buna	29 GPM	100	27 lbs.
YA NDP-20BST-D	3/4"	# Stainless/Teflon	29 GPM	100	37 lbs.

* Polypropylene Standpipe & Fittings. + Aluminum Standpipe & Fittings.

Stainless Standpipe & Fittings. † Kynar Standpipe & Fittings.

WE APPRECIATE YOUR
BUSINESS!


GPI Dual-Flo Piston Hand Pump

UL Listed • 50 Gallons per 100 Strokes

Will deliver more flow with greater ease than any other hand pump on the market. 2 quarts per stroke on lightweight fluids. Heavier fluids can be handled by moving the pivot pin on the handle which changes the stroke of the pump to deliver 1 quart per stroke. Lightweight aluminum body, stainless steel shaft and piston liner, a Teflon piston ring and packing, adjustable poly suction pipe, 2" MPT base, and a thermoplastic nozzle. 1" FPT inlet and 3/4" FPT outlet with 8' discharge hose and end spout.

HP100UL PETROLEUM PUMP: Suitable for B100 Biodiesel as well as gas and diesel.

Note: Not for E-85.



Part No. **GPI** HAND PUMPS Wt.
GI HP100UL Petro Pump 19 lbs.

304SS Rotary Hand Drum Pump

Stainless Steel Drum Pump is designed for use in dispensing and transferring chemicals and liquids including many acids, acetones, alcohols, trichloroethylene, solvents, photographic chemicals and ketones which are compatible with pump component materials.

- Investment Cast 304SS Construction with Carbon Vanes.
- Teflon Lip Seal.
- Maximum Temperature is 200° F.
- 6 GPM @ 70 RPM (12 oz./Stroke).
- 1-1/4" NPT x 40" Stainless Steel Suction Tube Assembly.
- 1" SS Discharge Spout (Non-Threaded).
- Stainless Steel Bung Adapter fits 1-1/2" to 2" NPT.
- Padlock Provision.



Part No. **GR** 5271-98 Wt.
GR 5271-98 Rotary Hand Pump 16 lbs.

Visit our office in Omaha, Nebraska



13808 Industrial Road • Omaha, NE 68137
1-800-228-9666 • 1-402-333-1444 • FAX: 1-402-333-5546

Visit our office in Davenport, Iowa



601 West 76th St. • Davenport, IA 52806
1-800-553-6975 • 1-563-386-0930 • FAX: 1-563-386-5448

Viton® is a registered trademark of DuPont Performance Elastomers