



Stainless Steel Centrifugal Pumps

Scot Pumps Stamped Stainless Steel Centrifugal Pumps can be used in an extremely wide and diverse array of applications. The possibilities are near endless for this pump line. *Scot Pumps* offer some of the highest quality stainless steel centrifugal pumps on the market. If you need added corrosion-resistance or simply want a top quality pump — don't look any further than *Scot Pumps*.



232



Motorpump 232

Motor Frame: J56
Motor Options: ODP, TEFC, Explosion-Proof
Motor RPM: 3500 or 1750
Inlet/Outlet: 1-1/2" x 1-1/4" FPT
Seal: Type 21 Mechanical Seal

HP Options: 2 - 5
Max. Flow: 115 GPM
Max. PSI: 68
Metallurgy: 304SS
Impeller Type: Enclosed

Please Call With Specifications For Pump Pricing

Part No.	Motor Type	RPM	Seal	Impeller	HP/PH	S.G.	Max GPM
SC 3400K111WPE	WEG TEFC	3500	Buna-Carbon/ Silicon-Carbide	6.3"	5HP / 3PH	1.00	140
SC 3400K129WPE	WEG TEFC	3500	Viton®-Silicon/Silicon-Carbide	6.3"	5HP / 3PH	1.00	140

Common Repair Kits:

Part No.	Description
SC 118-000-581	Buna Carbon-Ceramic, 3 Phase Repair Kit.....
SC 118-000-581E	Viton®-Carbon / Silicon-Carbide, 3 Phase Repair Kit.....
SC 118-000-581F	Viton® Silicon-Carbide/Silicon-Carbide, 3 Phase (Severe Duty)
SC 118-000-581-1	Buna Carbon-Ceramic, 1 Phase Repair Kit.....
SC 118-000-581E-1	Viton®-Carbon / Silicon-Carbide, 1 Phase Repair Kit.....
SC 118-000-581F-1	Viton® Silicon-Carbide/Silicon-Carbide, 1 Phase (Severe Duty)

*** Dultmeier Sales has full access to the Scot Pump product lines. Call with Your System Needs Today and we will be happy to source your pumps or repair items.*



Motorpump 236

Motor Frame: JM
Motor Options: ODP, TEFC, Explosion-Proof
Motor RPM: 3500 or 1750
Inlet/Outlet: 2" x 1-1/2" FPT
Seal: Type 21 Mechanical Seal

HP Options: 3 - 7.5
Max. Flow: 180 GPM
Max. PSI: 68
Metallurgy: 304SS
Impeller Type: Enclosed



236

Part No.	Ports	Motor Frame	Motor Type	RPM	Seal	Impeller	HP/PH	S.G.	Max. GPM
SC 3403K108BPE	2" x 1.5"	236JM	TEFC	3500	Buna/Carb/CM	5.8"	5HP / 3PH	1.00	160
SC 3403K112WPE	2" x 1.5"	236JM	TEFC	3500	Buna/Carb/CM	6.3"	7.5HP / 3PH	1.00	200
SC 3403K211WPE	2" x 1.5"	236JM	TEFC	3500	Viton®/Ceramic	4.8"	5HP / 3PH	1.25	135

*** Suffix 'PE' denotes premium efficient motor for greater longevity and lower operating costs.*

** More options available – call with specifications. Dultmeier Sales has full access to the Scot Pump product lines.*

† 1.0 S.G. (Specific Gravity) is for water only; 1.25 S.G. is for liquids up to 10.4 Lbs./Gal. - Call for heavier products.

Common Repair Kits:

Part No.	Description
SC 118-000-605	Buna Carbon-Ceramic Repair Kit.....
SC 118-000-605A	Viton-Carbon / Silicon-Carbide Repair Kit.....



Motorpump 320



320

Motor Frame: JM
Motor Options: ODP, TEFC, Explosion-Proof
Motor RPM: 3500
Inlet/Outlet: 2" x 1-1/4" Flange
Seal: Type 21 Mechanical Seal

HP Options: 2 - 5
Max. Flow: 150 GPM
Max. PSI: 51
Metallurgy: 304SS
Impeller Type: Enclosed

Please Call With Specifications For Pump Pricing

Common Repair Kits:

Part No.	Description
SC 118-000-673	Buna Carbon Ceramic Repair Kit.....
SC 118-000-673A	Viton® Carbon Ceramic Repair Kit.....

*** Dultmeier Sales has full access to the Scot Pump product lines. Call with Your System Needs Today and we will be happy to source your pumps or repair items.*

Viton® is a registered trademark of DuPont Performance Elastomers

