

REELCRAFT**Power Cord Reels****Spring Rewind Power Cord Reels**

have a compact design for critical space requirements. Corrosion-resistant, baked-on finish. Can be mounted to wall, ceiling or bench. Supplied with 4' inlet cord, power cord, hose guide and cord stop.

L4050-1633



Part No.	Cord Length	Rating	Wt.
RF L4050-1633	50'	13 Amp / 115 Volt	26 lbs.
RF L4545-1233	45'	15 Amp / 115 Volt	28 lbs.
RF L4545-1233A	45'	20 Amp / 125 Volt	29 lbs.

REELCRAFT**High Temperature Rinse Rewind Reel****Rewind Rinse Down Reel**

from Reelcraft is ideal for high temperature rinsing applications. Standard with 3/8" x 35' hose and trigger spray rinse valve. Buna seal. Rated to 180° F. and 125 PSI. Inlet is 3/8" FPT. Compact size is 14-1/4" high x 14-1/4" deep x 6" wide. **Made in USA.**



Part No.	Pressure	Temperature	Wt.
RF 5635OLPSW5	125 PSI	180° F.	27 lbs.



CU6050LN

REELCRAFT**Light Duty Air Hose Reels**

Light-Duty Steel Reels are an ideal choice for air supply lines in shops or garages. Hand crank design with balanced brass swivel.

Inlet and outlet are 3/8" FPT. Rated to 250 PSI. Can be mounted on floor or wall. Both reels are 11-1/2" high x 11" deep. *Hose is not included.*



CU6100LN


Part No.	Hose Capacity	Width	Wt.
RF CU6050LN	50' of 3/8" I.D.	17-1/4"	10 lbs.
RF CU6100LN	100' of 3/8" I.D.	21"	13 lbs.

Stainless Steel Spring Rewind Reels**REELCRAFT****Corrosion-Resistant, Stainless Spring Rewind Hose Reels**

from Reelcraft. Ideal for use in food processing, wash down, industrial use, off-shore and on board marine applications or anywhere harsh environments require stainless construction. Swivels with Viton® o-rings are standard. Rated to 500 PSI and 210° F. (*Hoses are not included.*)



7800OLS



Part No.	Hose Capacity	Maximum Pressure	Wt.
RF 7800OLS	1/2" x 50'	500 PSI	41 lbs.
RF 82000OLS	1/2" x 100'	500 PSI	81 lbs.
RF D83000OLS	3/4" x 75'	500 PSI	84 lbs.
RF D84000OLS	1" x 50'	500 PSI	92 lbs.

Enclosed Air Reel**Standard Features:**

- Allows for 50' of Capacity
- Hose Inlet/Outlet is 3/8"
- Working Pressure of 300 PSI
- Advanced Auto Stop & Automatic Guide System
- Hose Can Be Stopped at Any Point & a Controlled Return Allows the Hose to Safely Guide Back Into the Enclosed Housing
- Compatible with Air or Water
- Bracket Allows for 180° of Swivel
- 3/8" x 50' of Hose Included



Part No.	Description
NS 1459NS	3/8" x 50' Enclosed Hose Reel, Spring Return ...



Viton® is a registered trademark of DuPont Performance Elastomers

