



Gruvlok® Fittings

Victaulic®-Style Grooved Fittings for commercial/industrial construction, water transfer, and fire protection plumbing. Constructed of ductile iron with rust-inhibiting paint. Buna gaskets are standard unless noted (*EPDM & Viton® also available on most fittings*). All fittings UL and FM approved. Maximum operating pressures at 70° F. noted below. **Other sizes are available to those shown.**

Groove Dimensions					
Size	OD	A	B	C	D
1 1/2"	1.900	5/8	5/16	1.775	1.900
2"	2.375	5/8	5/16	2.250	2.375
2 1/2"	2.875	5/8	5/16	2.750	2.875
3"	3.000	5/8	5/16	3.384	3.500
4"	4.500	5/8	3/8	4.334	4.500
6"	5.563	5/8	3/8	5.395	5.563
8"	6.625	5/8	3/8	6.405	6.625
8"	6.625	3/4	7/16	6.441	6.625
10"	10.750	3/4	1/2	10.562	10.750
12"	12.750	3/4	1/2	12.531	12.750

Standard Couplings

1000 PSI for 1-1/2"-6" • 800 PSI for 8" - 12"



Part No.	Size
EV GC15	1-1/2"
EV GC2	2"
EV GC25	2-1/2"
EV GC3	3"
EV GC4	4"
EV GC6	6"
EV GC8	8"

Lightweight Flexible Couplings

500 PSI for 1-1/2" & 2" • 300 PSI for 2-1/2" - 12"

Part No.	Size
EV GFC15	1-1/2"
EV GFC2	2"
EV GFC25	2-1/2"
EV GFC3	3"
EV GFC4	4"
EV GFC6	6"
EV GFC8	8"



Rigid Couplings - 175 PSI -




Part No.	Size
EV GRC2	2"
EV GRC3	3"
EV GRC4	4"
EV GRC6	6"

Quick Release Couplings

- 300 PSI -

Part No.	Size
EV QCC2	2"
EV QCC3	3"
EV QCC4	4"
EV QCC6	6"



Includes Steel Safety Pin

ANSI Split Flange Couplings

300 PSI • EPDM Gaskets • ANSI 125/150



Part No.	Size
EV GSF2	2"
EV GSF3	3"
EV GSF4	4"
EV GSF6	6"

45° Elbows - 1000 PSI -

Part No.	Size
EV GL45-2	2"
EV GL45-25	2-1/2"
EV GL45-3	3"
EV GL45-4	4"
EV GL45-6	6"
EV GL45-8	8"



90° Elbows - 1000 PSI -



Part No.	Size
EV GL90-2	2"
EV GL90-25	2-1/2"
EV GL90-3	3"
EV GL90-4	4"
EV GL90-6	6"
EV GL90-8	8"

Tees - 1000 PSI -



Part No.	Size
EV GT2	2"
EV GT25	2-1/2"
EV GT3	3"
EV GT4	4"
EV GT6	6"
EV GT8	8"

Mechanical Tees

1000 PSI • EPDM Gaskets

Part No.	Size
EV GMT2X1	2" x 1" Branch
EV GMT3X1	3" x 1" Branch
EV GMT4X2	4" x 2" Branch
EV GMT4X3	4" x 3" Branch



Reducers - 1000 PSI -



Part No.	Size
EV GR-3X2	3" x 2"
EV GR-4X2	4" x 2"
EV GR-4X3	4" x 3"
EV GR-6X4	6" x 4"

ANSI Flange Adapters


300 PSI • ANSI 125/150

ANSI Flange Adapters

Part No.	Size
EV GFA2	2"
EV GFA3	3"
EV GFA4	4"
EV GFA6	6"
EV GFA8	8"



End Caps - 1000 PSI -



Part No.	Size
EV GEC2	2"
EV GEC3	3"
EV GEC4	4"
EV GEC6	6"

Gaskets

Buna gaskets are temperature rated between -24° F. to +175° F. EPDM and Viton® also available.

Part No.	Size	Material
EV G200T	2"	Buna
EV G300T	3"	Buna
EV G400T	4"	Buna
EV G600T	6"	Buna



Grooved End Nipples Carbon & 316 Stainless

Designed to provide minimum pressure drop and uniform strength. Available styles: Long Pipe (MPT), Weld End and King Hose Barb.



Part No.	Size	Style	Material
EV RSTV25	2"	King Nipple	316 SS
EV GWE2	2"	Weld End	CS
EV GLP3	3"	Long Pipe (4" L)	CS
EV RSTV35	3"	King Nipple	316 SS
EV GWE3	3"	Weld End	CS
EV GLP4	4"	Long Pipe (6" L)	CS
EV RSTV40	4"	King Nipple	316 SS
EV GWE4	4"	Weld End	CS

Call for Current Pricing