



AMT Cast Stainless Centrifugal Pump Units

- 300 Series Investment Cast Stainless Steel Housing & Impellers
- Vitor® Mechanical Seal and O-Ring.
- Optional Silicon Carbide Mechanical Seals Available.
- Discharge Port Rotates in 90° Increments.
- 489 Series: 1-1/4" x 1" Ports.
- 490 Series: 1-1/2" x 1 1/4" Ports.
- Max. Temperature 200° F.
- Max. Flow 145 GPM.
- Max. Head 55 PSI.
- Self-Cleaning, Semi-Open Impellers.
- Totally Enclosed Fan Cooled (TEFC) 56J Motors.
- 1/2 HP to 3 HP Single and Three Phase 3450 RPM Motors.



Part No.	Ports	Max GPM	GPM @			Voltage
			15 PSI	HP	Phase	
GR 369C-98	1-1/4" x 1"	76	40	1.0	1	115/230V
GR 369F-98	1-1/4" x 1"	76	40	1.0	3	230/460V
GR 369D-98	1-1/4" x 1"	92	48	2.0	1	115/230V
GR 369E-98	1-1/4" x 1"	92	48	2.0	3	230/460V
GR 5030-98	1-1/2" x 1"	145	135	3.0	1	208/230V
GR 5031-98	1-1/2" x 1"	145	135	3.0	3	208-230/460V

Note: All models for use with non-viscous liquids with specific gravity of 1.15 or less (9.6 lbs/gal)